JUST ROLL





PALMERA
FURNITURE





YORK'S JUST ROLL COLLECTION OFFERS A WIDE RANGE TO SUITE ANY REQUIREMENT

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

PALMERA
FURNITURE



BLACKOUT SCREENS

TECNICAL SPECIFICATIONS

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	LIGHT FASTNESS	CARE INSTRUCTION
JR001	45% POLYESTER 40% COTTON 5% LINEN	300 CM	380 GSM	0.45 MM	20 MT	BLACKOUT	5-6	DAMP SPONGE
JR002 TO JR003	100% POLYESTER	300 CM	395 GSM	0.64 MM	20 MT	BLACKOUT	4-5	DAMP SPONGE
JR004 TO JR008	100% POLYESTER	300 CM	345 GSM	0.46 MM	30 MT	BLACKOUT	4-5	DO NOT SCRUB DON'T USE SOLVENTS DAMP SPONGE ONLY

OPTICAL AND THERMAL PERFORMANCES

	Fabric												Fabric + Glazing											
	Visible Light EN 410			Classification EN 14501				N.E.S.W.	Solar Heat EN 410				Reference Glazings EN ISO 52022-1 / EN 14501											
													Glazing B*			Glazing C*			Glazing D*			Glazing E*		
	Tv	Rv	Av	Glare Control	Outdoor Visibility	Night Privacy	Daylight Utilisation	Workstation Orientation**	Ts	Rs	As	Tuv	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class
JR001	0%	79%	21%	4	0	4	0		0%	69%	31%	0%	0,33	0,43	2	0,34	0,58	2	0,25	0,78	2	0,34	0,62	2
JR002	0%	79%	21%	4	0	4	0		0%	67%	33%	0%	0,34	0,45	2	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR003	0%	79%	21%	4	0	4	0		0%	67%	33%	0%	0,34	0,45	2	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR004	0%	79%	21%	4	0	4	0		0%	67%	33%	0%	0,34	0,45	2	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR005	0%	79%	21%	4	0	4	0		0%	67%	33%	0%	0,34	0,45	2	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR006	0%	79%	21%	4	0	4	0		0%	69%	31%	0%	0,33	0,43	2	0,34	0,58	2	0,25	0,78	2	0,34	0,62	2
JR007	0%	79%	21%	4	0	4	0		0%	67%	33%	0%	0,34	0,45	2	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR008	0%	79%	21%	4	0	4	0		0%	67%	33%	0%	0,34	0,45	2	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2

ECO FRIENDLY/100% RECYCLABLE/ENERGY SAVING/PVC FREE/LEAD FREE/FORMALDEHYDE FREE/VOC FREE/PHTALATES FREE

JR001

JR002

JR003

JR004

JR005

JR006

JR007

JR008



PALMERA
FURNITURE



OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

PALMERA
FURNITURE

ECO FRIENDLY · 100% RECYCLABLE · ENERGY SAVING · PRINTABLE · PVC FREE · LEAD FREE · FORMALDEHYDE FREE · VOC FREE · PHTALATES FREE

SHEER SCREENS

TECNICAL SPECIFICATIONS

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	CARE INSTRUCTION
JR009 TO JR012	100% POLYESTER	300 CM	135 GSM	0.36 MM	30 MT	SHEER	DO NOT SCRUB DON'T USE SOLVENTS DAMP SPONGE ONLY
JR013 TO JR016	100% POLYESTER	300 CM	115 GSM	0.25 MM	30 MT	SHEER	DO NOT SCRUB DON'T USE SOLVENTS DAMP SPONGE ONLY

ECO FRIENDLY/100% RECYCLABLE/ENERGY SAVING/PVC FREE/LEAD FREE/FORMALDEHYDE FREE/VOC FREE/PHTALATES FREE




















PALMERA
FURNITURE

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

PALMERA
FURNITURE

ECO FRIENDLY · 100% RECYCLABLE · ENERGY SAVING · PAINTABLE · PVC FREE · LEAD FREE · FORMALDEHYDE FREE · VOC FREE · PHTALATES FREE

DIMOUT SCREENS

TECNICAL SPECIFICATIONS

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	CARE INSTRUCTION
JR017 TO JR021	100% POLYESTER	300 CM	170 GSM	0.32 MM	30 MT	SHEER	DO NOT SCRUB DON'T USE SOLVENTS DAMP SPONGE ONLY

OPTICAL AND THERMAL PERFORMANCES

	Fabric													Fabric + Glazing											
	Visible Light EN 410			Classification EN 14501				N.E.S.W.	Solar Heat EN 410					Reference Glazings EN ISO 52022-1 / EN 14501											
														Glazing B*			Glazing C*			Glazing D*			Glazing E*		
	Tv	Rv	Av	Glare Control	Outdoor Visibility	Night Privacy	Daylight Utilisation	Workstation Orientation**	Ts	Rs	As	Tuv		Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class
JR017	16%	80%	4%	2	0	2	2		18%	74%	8%	1%	0,33	0,43		2	0,33	0,56	2	0,25	0,78	2	0,33	0,60	2
JR018	14%	83%	3%	3	0	3	2		16%	75%	9%	1%	0,32	0,42		2	0,33	0,56	2	0,25	0,78	2	0,33	0,60	2
JR019	16%	79%	5%	2	0	2	2		18%	73%	9%	1%	0,33	0,43		2	0,34	0,58	2	0,25	0,78	2	0,33	0,60	2
JR020	6%	51%	43%	4	0	3	1		14%	59%	27%	0%	0,40	0,53		1	0,38	0,64	1	0,26	0,81	2	0,37	0,67	1
JR021	3%	43%	54%	4	0	4	0		5%	42%	53%	0%	0,47	0,62		1	0,43	0,73	1	0,27	0,84	2	0,42	0,76	1

ECO FRIENDLY/100% RECYCLABLE/ENERGY SAVING/PVC FREE/LEAD FREE/FORMALDEHYDE FREE/VOC FREE/PHTALATES FREE

JR017

JR018

JR019

JR020

JR021



PALMERA
FURNITURE

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

PALMERA
FURNITURE



3% OPENNESS SCREENS

TECNICAL SPECIFICATIONS

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	FIRE RETARDENCY	CARE INSTRUCTION
JR022 TO JR025	85% RECYCLED POLYESTER 15% VIRGIN POLYESTER	300 CM	425 GSM	0.55 MM	30 MT	3%	NFPA701, CA TITLE 19	DO NOT SCRUB DON'T USE SOLVENTS DAMP SPONGE ONLY
JR026 TO JR029	100% POLYESTER	300 CM	230 GSM	0.36 MM	30 MT	3%		DO NOT SCRUB DON'T USE SOLVENTS DAMP SPONGE ONLY

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	FIRE RETARDENCY	LIGHT FASTNESS	CARE INSTRUCTION
JR030 TO JR032	100% POLYESTER	300 CM	380 GSM	0.54 MM	30 MT	3%	NFPA 701, DIN 4102 B1, BS 5867 PART 2 TYPE B, NF P92-503 M1	6-7	DAMP SPONGE

OPTICAL AND THERMAL PERFORMANCES

	Fabric												Fabric + Glazing											
	Visible Light EN 410			Classification EN 14501				N.E.S.W.	Solar Heat EN 410				Reference Glazings EN ISO 52022-1 / EN 14501											
													Glazing B*			Glazing C*			Glazing D*			Glazing E*		
	Tv	Rv	Av	Glare Control	Outdoor Visibility	Night Privacy	Daylight Utilisation	Workstation Orientation**	Ts	Rs	As	Tuv	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class
JR022	26%	70%	4%	0	0	2	3		26%	67%	7%	8%	0,36	0,47	1	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR023	20%	62%	18%	0	0	2	2		22%	61%	17%	6%	0,38	0,50	1	0,37	0,63	1	0,25	0,78	2	0,36	0,65	1
JR024	17%	57%	26%	0	1	2	2		19%	56%	25%	7%	0,41	0,54	1	0,38	0,64	1	0,25	0,78	2	0,37	0,67	1
JR025	6%	29%	65%	2	1	2	1		7%	27%	66%	4%	0,53	0,70	0	0,47	0,80	1	0,28	0,88	2	0,45	0,82	1
JR026	20%	62%	18%	0	0	2	2		22%	61%	17%	6%	0,38	0,50	1	0,37	0,63	1	0,25	0,78	2	0,36	0,65	1
JR027	20%	62%	18%	0	0	2	2		22%	61%	17%	6%	0,38	0,50	1	0,37	0,63	1	0,25	0,78	2	0,36	0,65	1
JR028	17%	57%	26%	0	1	2	2		19%	56%	25%	7%	0,41	0,54	1	0,38	0,64	1	0,25	0,78	2	0,37	0,67	1
JR029	6%	29%	65%	2	1	2	1		7%	27%	66%	4%	0,53	0,70	0	0,47	0,80	1	0,28	0,88	2	0,45	0,82	1
JR030	26%	70%	4%	0	0	2	3		26%	67%	7%	8%	0,36	0,47	1	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR031	20%	62%	18%	0	0	2	2		22%	61%	17%	6%	0,38	0,50	1	0,37	0,63	1	0,25	0,78	2	0,36	0,65	1
JR032	10%	42%	48%	0	1	2	1		11%	41%	48%	5%	0,47	0,62	1	0,42	0,71	1	0,26	0,81	2	0,41	0,75	1

ECO FRIENDLY/100% RECYCLABLE/ENERGY SAVING/PVC FREE/LEAD FREE/FORMALDEHYDE FREE/VOC FREE/PHTALATES FREE

JR022

JR023

JR024

JR025

JR026

JR027

JR028

JR029

JR030

JR031

JR032



PALMERA
FURNITURE

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

PALMERA
FURNITURE



5% OPENNESS SCREENS

TECNICAL SPECIFICATIONS

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	FIRE RETARDENCY	CARE INSTRUCTION
JR033 TO JR036	85% RECYCLED POLYESTER 15% VIRGIN POLYESTER	300 CM	330 GSM	0.48 MM	30 MT	5%	NFPA701, CA TITLE 19	DO NOT SCRUB DON'T USE SOLVENTS DAMP SPONGE ONLY

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	FIRE RETARDENCY	LIGHT FASTNESS	CARE INSTRUCTION
JR037 TO JR039	100% POLYESTER	300 CM	295 GSM	0.65 MM	30 MT	5%	NFPA 701, DIN 4102 B1, BS 5867 PART 2 TYPE B, NF P92-503 M1	5-6	DAMP SPONGE


OPTICAL AND THERMAL PERFORMANCES

	Fabric													Fabric + Glazing										
	Visible Light EN 410			Classification EN 14501				N.E.S.W.	Solar Heat EN 410				Reference Glazings EN ISO 52022-1 / EN 14501											
													Glazing B*			Glazing C*			Glazing D*			Glazing E*		
	Tv	Rv	Av	Glare Control	Outdoor Visibility	Night Privacy	Daylight Utilisation	Workstation Orientation**	Ts	Rs	As	Tuv	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class
JR033	19%	42%	39%	0	2	1	2		26%	51%	23%	13%	0,44	0,58	1	0,40	0,68	1	0,26	0,81	2	0,39	0,71	1
JR034	17%	45%	38%	0	1	2	2		23%	52%	25%	8%	0,43	0,57	1	0,39	0,66	1	0,26	0,81	2	0,38	0,69	1
JR035	17%	45%	38%	0	1	2	2		23%	52%	25%	8%	0,43	0,57	1	0,39	0,66	1	0,26	0,81	2	0,38	0,69	1
JR036	8%	14%	78%	1	3	1	1		18%	37%	45%	7%	0,49	0,64	1	0,44	0,75	1	0,27	0,84	2	0,42	0,76	1
JR037	17%	45%	38%	0	1	2	2		23%	52%	25%	8%	0,43	0,57	1	0,39	0,66	1	0,26	0,81	2	0,38	0,69	1
JR038	13%	39%	48%	0	1	2	2		21%	49%	30%	8%	0,44	0,58	1	0,40	0,68	1	0,26	0,81	2	0,39	0,71	1
JR039	11%	30%	59%	1	2	1	1		20%	45%	35%	8%	0,46	0,61	1	0,42	0,71	1	0,26	0,81	2	0,40	0,73	1

ECO FRIENDLY/100% RECYCLABLE/PRINTABLE /ENERGY SAVING/PVC FREE/LEAD FREE/
FORMALDEHYDE FREE/VOC FREE/PHTALATES FREE/FR(NFPA701)


















PALMERA
FURNITURE

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

PALMERA
FURNITURE



7% OPENNESS SCREENS

TECNICAL SPECIFICATIONS

SERIAL NO	COMPOSITION	WIDTH	WEIGHT	THICKNESS	ROLL LENGTH	OPENNESS	FIRE RETARDENCY	LIGHT FASTNESS	CARE INSTRUCTION
JR040 TO JR042	100% POLYESTER	300 CM	400 GSM	0.65 MM	25 MT	7%	NFPA 701, DIN 4102 B1, BS 5867 PART 2 TYPE B, NF P92-503 M1	6-7	DAMP SPONGE

OPTICAL AND THERMAL PERFORMANCES

	Fabric												Fabric + Glazing											
	Visible Light EN 410			Classification EN 14501				N.E.S.W.	Solar Heat EN 410				Reference Glazings EN ISO 52022-1 / EN 14501											
													Glazing B*			Glazing C*			Glazing D*			Glazing E*		
	Tv	Rv	Av	Glare Control	Outdoor Visibility	Night Privacy	Daylight Utilisation	Workstation Orientation**	Ts	Rs	As	Tuv	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class	Gtot	Fc	Class
JR040	26%	70%	4%	0	1	1	3		27%	67%	6%	12%	0,36	0,47	1	0,35	0,59	1	0,25	0,78	2	0,34	0,62	2
JR041	17%	58%	25%	0	2	1	2		21%	61%	18%	8%	0,38	0,50	1	0,37	0,63	1	0,25	0,78	2	0,36	0,65	1
JR042	16%	49%	35%	0	2	1	2		22%	57%	21%	10%	0,40	0,53	1	0,38	0,64	1	0,25	0,78	2	0,37	0,67	1

ECO FRIENDLY/100% RECYCLABLE/PRINTABLE /ENERGY SAVING/PVC FREE/LEAD FREE/
FORMALDEHYDE FREE/VOC FREE/PHTALATES FREE/FR(NFPA701)

JR040

JR041

JR042



PALMERA
FURNITURE



JUST ROLL

These articles have undergone special dyeing and washing process to obtain an authentic look.
This gives the fabric a distinctive appearance and a beautiful soft texture.
Every meter is unique, therefore there can be variations in colour and shading which is indicative of this process.
We recommend that each colour should be dry cleaned separately.

If an exact match is required please request stock cutting.

PALMERA
FURNITURE